

METHOD OF PRODUCING WHITE NOISE, CONTROL METHOD OF WHITE NOISE AMPLITUDE, AND DIGITAL TELEPHONE SYSTEM

Publication number: JP2000081898 (A)

Publication date: 2000-03-21

Inventor(s): SUZUKI KUNIKAZU

Applicant(s): DENSO CORP

Classification:

- International: G10L19/08; G10L19/00; H03B29/00; H04J13/00; G10L19/00; H03B29/00; H04J13/00; (IPC1-7): G10L19/08; G10L19/00; H03B29/00; H04J13/00


- European:

Application number: JP19980249839 19980903

Priority number(s): JP19980249839 19980903

Abstract of JP 2000081898 (A)

PROBLEM TO BE SOLVED: To realize a white noise producing method capable of preventing a jar from being generated. **SOLUTION:** When, a frame to be processed is in a frame error state, a last effective frame before the frame to be processed is full-rated or half-rated, and a mean adaptive code book gain value is less than 0.4 at the time and a mean fixed code book gain value exceeds a threshold, white noise (S(n)) is generated by generating an additional exciting signal by using, instead of the mean fixed code book gain, a prescribed constant with which the amplitude value of an exciting signal after synthesis ($E_t'(n)$) becomes less than a constant value, adding the additional exciting signal to an exciting signal before synthesis ($E_t(n)$), and processing the exciting signal after synthesis ($E_t'(n)$) by synthesis-filtering operation.; Consequently, it is possible to control the amplitude of the white noise (S(n)) by controlling the amplitude of the exciting signal after synthesis ($E_t'(n)$) outputted from a vocoder 4, and prevent jarring noise from being generated.



Data supplied from the esp@cenet database — Worldwide

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2000-081898

(43)Date of publication of application : 21.03.2000

(51)Int.Cl. G10L 19/08

G10L 19/00

H03B 29/00

H04J 13/00

(21)Application number : 10-249839

(71)Applicant : DENSO CORP

(22)Date of filing : 03.09.1998

(72)Inventor : SUZUKI KUNIKAZU

(54) METHOD OF PRODUCING WHITE NOISE, CONTROL METHOD OF WHITE NOISE AMPLITUDE, AND DIGITAL TELEPHONE SYSTEM

(57)Abstract:

PROBLEM TO BE SOLVED: To realize a white noise producing method capable of preventing a jar from being generated.

SOLUTION: When, a frame to be processed is in a frame error state, a last effective frame before the frame to be processed is full-rated or half-rated, and a mean adaptive code book gain value is less than 0.4 at the time and a mean fixed code book gain value exceeds a threshold, white noise ($S(n)$) is generated by generating an additional exciting signal by using, instead of the mean fixed code book gain, a prescribed constant with which the amplitude value of an exciting signal after synthesis ($Et'(n)$) becomes less than a constant value, adding the additional exciting signal to an exciting signal before synthesis ($Et(n)$) to generate the exciting signal after synthesis ($Et'(n)$), and processing the exciting signal after synthesis ($Et'(n)$) by synthesis-filtering operation.

Consequently, it is possible to control the amplitude of the white noise ($S(n)$) by controlling the amplitude of the exciting signal after synthesis ($Et'(n)$) outputted from a vocoder 4, and prevent jarring noise from being generated.

